```
ANSWER 1 OF 2 WPIX COPYRIGHT 2007
                                          THE THOMSON CORP on STN
     1985-267645 [43]
                        WPIX
AN
DNC
    C1985-116198 [21]
    Melt spinning pack - containing filter medium in net including sintered
тT
    metal, and particulate filtering medium of silica, covered with cured
     modified silicone
     A26; A31; A88; F01
DC
     KATO T; KUWABARA M; TAKEDA T
IN
     (TORA-C) TORAY IND INC
PA
CYC 1
                    A 19850917 (198543)* JA 6[0]
PΙ
     JP 60181309
                                                                           ---
    JP 05032487
                   B 19930517 (199322) JA 7
    JP 60181309 A JP 1984-35888 19840229; JP 05032487 B JP
ADT
     1984-35888 19840229
    JP 05032487 B Based on JP 60181309 A
PRAI JP 1984-35888 19840229
     ICM D01D001-10
TPCR B01D0039-02 [I,C]; B01D0039-06 [I,A]; D01D0001-00 [I,C]; D01D0001-10
     [I,A]; D01D0004-00 [I,C]; D01D0004-04 [I,A]
     JP 60181309 A
                   UPAB: 20050426
     Pack contains filtering medium in plate of net and filter medium in
     particles all of which are covered with a cured film of modified silicone.
     Pref. modified silicone is a silicone resin which has reactive functional
     qp. other than alkyl qp. in side chain at terminal and can be cured at a
     relatively low temperature of below 300 deg.C such as methyl hydrodiene
     and alcohol (epoxy, carbinol, amino) -modified silicone. It is applied in
     0.001 to 5.0, pref. 0.01 to 1.0 weight% of filtering medium. The filtering
     medium in plate of net includes sintered metal, filter, sintered metal
    net, etc. The particulate filtering medium consists of alumina, stainless
     steel, glass bead, silica sand, etc.
           ADVANTAGE - Used for filtration of molten thermoplastic polymer for
     melt spinning. Decomposition or crosslinking of molten polymer is
     prevented and loss of spun fibre due to end breakage, etc. especially in
initial
     stage of spinning is minimised.
     CPI: A06-A00E2; A10-G01; A11-B15B; A12-H04; A12-S05L; F01-C; F01-C01;
           F01-C03
     ANSWER 2 OF 2 JAPIO (C) 2007 JPO on STN
L4
AN
     1985-181309
                    JAPIO
ΤI
     MELT SPINNING PACK
IN
     TAKEDA TOSHIYUKI; KUWABARA MASATO; KATO TETSUYA
PΔ
     TORAY IND INC
     JP 60181309 A 19850917 Showa
PΙ
     JP 1984-35888 (JP59035888 Showa) 19840229
AΙ
PRAI JP 1984-35888
                         19840229
     PATENT ABSTRACTS OF JAPAN (CD-ROM), Unexamined Applications, Vol. 1985
IC
     ICM D01D001-10
     ICS B01D039-06; D01D004-04
     PURPOSE: A melt spinning pack, obtained by forming fixed films prepared by
     curing a modified silicone on the respective surfaces of a plate or
     netlike filter medium and granular filter medium, useful for filtration
     members for molten polymers, and capable of preventing broken yarns during
     spinning and deterioration in yarn quality.
     CONSTITUTION: A melt spinning pack, obtained by packing a plate and
     netlike filter material and a granular filter medium therein, and applying
     and forming cured fixed films of a modified silicone, e.g.
     methylhydrogensilicone, on the surfaces of the above-mentioned filter
```

material and the above-mentioned filter medium in an amount of 0.01&sim,1.0wt% for the filter material and 0.05&sim,0.5wt% for the filter

medium.
USE: Suitable for melt spinning of thermoplastic synthetic polymers, e.g. polyamide or polyester, easily decomposable at relatively high temperatures.
COPYRIGHT: (C)1985,JPO&Japio

=>